

PeBBLE

The color card printer
The best quality/price ratio on the market



Color & Monochrome
Thermal Transfer



300 dpi



Single-Sided



24 s/card



0.25-1 mm
(10-40 mil)



2 years

evolis

www.evolis.com

Pebble



Powerful, easy-to-use and cost-effective, the **Pebble** color printer personalizes and encodes all your plastic cards: identification, security, loyalty and leisure badges.

The **Pebble** prints your high resolution texts, logos, pictures, signatures and barcodes in a few seconds. It also offers optional magnetic encoding, smart card encoding and contactless card personalization.

Powerful and reliable, the **Pebble** is designed to answer all needs, from small card series to printing in volume.

The **Pebble** is a turnkey solution. Delivered as standard with user-friendly software for badge personalization and drivers for Windows™ or Mac OS X, it is as easy-to-use as a classical office printer.

The **Pebble** comes in three colors: Lagoon, Ruby and Glacier. Its Hi-Tech design, compactness and ergonomics allow it to integrate any reception or office desk.

With an excellent quality/price ratio, the **Pebble** is **the referent single-sided color printer on the market**.



Print mode

- Color dye sublimation and monochrome thermal transfer
- Edge-to-edge printing standard

Printer specifications

- Integrated ribbon saver for monochrome printing

Print speed

- 150 cards/hour in full color (YMCKO)
- Up to 1000 cards/hour in monochrome¹

Resolution

- 300 dpi (11,8 dots/mm)

Printer colors

- Glacier, Lagoon or Ruby

Software supplied

- eMedia Card Designer for designing and editing badges
- Compatible with Windows™ 95, 98, NT 4.0, 2000 and Xp

Drivers

- **For Windows™** 95, 98, NT 4.0, 2000 and Xp
- **For Mac™** OS X v10.2 and v10.3

Warranty

- Printer: 2 years
- Print head: 2 years, unlimited number of prints²

Ribbon types

- Monochrome ribbon: 1000 cards/roll (black, blue, red, green, white, gold, silver and scratch off)
- BlackWAX monochrome ribbon (for ABS and special varnished plastic cards): 1000 cards/roll
- 2 panel black monochrome ribbon (KO): 500 cards/roll
- 5 panel color ribbon (YMCKO): 200 cards/roll
- Half-panel color ribbon (YMCKO): 400 cards/roll
- Hologram ribbon: 350 cards/roll

Card loading modes

- Automatic with feeder or hand-feed

Options

- HICO/LOCO magnetic stripe encoder (3-tracks), ISO 7811, field upgradeable
- Serial port (available upon study)
- Hand-feed cartridge
- 100-card additional feeder
- Suitcase for demonstration
- Cleaning kit

Other printer models

- **Pebble Mag** - Printer with HICO/LOCO magnetic stripe encoder - ISO 7811
- **Pebble Smart** - Printer with smart card contact station - ISO 7816-2
- **Pebble Contactless** - Printer with contactless smart card coupler - ISO 14443 - ISO 15693 (other standards upon request)

1 - Under specific conditions 2 - Clause governing the use of Evolis ribbons



Card types

Card format

Card thickness

Card feeder capacity

Card output hopper capacity

Resident barcodes

Resident fonts

Printer size

Printer weight

Connections

Electrical

Environmental

PVC, Composite PVC, PET, ABS and special varnished plastic cards

ISO CR-80 - ISO 7810 (53,98 mm x 85,60 mm - 3.375" x 2.125")

From 0,25 mm (10 mil) to 1 mm (40 mil)

300 cards (0,25 mm - 10 mil) - 100 cards (0,76 mm - 30 mil)

150 cards (0,25 mm - 10 mil) - 50 cards (0,76 mm - 30 mil)

Code 39, Code 2/5 interleaved

Arial normal 100, Arial bold 100

Height: 192 mm (7.55") - Length: 396 mm (15.59") - Width: 235 mm (9.25")

5,9 Kg (13 lbs)

USB and Centronics parallel ports (cables supplied)

110-230 Volts CA, 60-50 Hertz

- Min / max operating temperature: 15° / 30° C (59° / 86° F)

- Humidity: 20% to 65% non-condensing

- Min / max storage temperature: -5° / +70° C (23° / 158° F)

- Storage humidity: 20% to 70% non-condensing

- Operating ventilation: free air



Branch office for the Americas:
Evolis Inc.

1835 South Perimeter Road · Suite 190 · Fort Lauderdale · FL 33309 · USA
Tel: (954) 491-9898 · Fax: (954) 491-5140 · evolisinc@evolis.com

Headquarters:
Evolis Card Printer

29, Avenue de la Fontaine · Z.I. Angers-Beaucouzé · 49070 Beaucouzé · France
Tel: +33 (0) 241 367 606 · Fax: +33 (0) 241 367 612 · info@evolis.com